

VEGA

SINGLE-PHASE

0.3-25kVA



Standard features

Selectable output voltage (dip switch)*	220-230-240V
Frequency	50Hz $\pm 5\%$ or 60Hz $\pm 5\%$
Output voltage accuracy	$\pm 0,5\%$
Admitted load variation	Up to 100%
Cooling	Natural ventilation
Ambient temperature	-25/+45°C
Storage temperature	-25/+60°C
Max relative humidity	<95% (non condensing)
Admitted overload	200% 2min.
Harmonic distortion	None introduced
Colour	RAL 7035
Protection degree	IP 21
Instrumentation	Output digital voltmeter
Installation	Indoor

* Output voltage can be adjusted by choosing one of the indicated values.
Such choice sets the new nominal value as a reference for all the stabiliser parameters.

Ratings in relation to the input variation percentage

$\pm 15\%$	$\pm 20\%$	$\pm 25\%$	$\pm 30\%$	+15/-25%	+15/-35%	+15/-45%
1	0.7	0.5	0.3	0.7	0.5	0.3
2.5	2	1.5	1	2	1.5	1
5	4	3	2	4	3	2
7	5	4	3	5	4	3
10	7	5	4	7	5	4
15	10	7	5	10	7	5
20	15	10	7	15	10	7
25	20	15	10	20	15	10

Accessories

Interrupting devices
Load protection against over/undervoltage
Manual by-pass line
Input isolating transformer
SPD surge arrester
EMI/RFI filters
Up to IP55 protection degree for indoor and outdoor installation



All ORTEA equipments are designed and built in compliance with the Low Voltage and Electromagnetic Compatibility European Directives with regard to the CE marking requirements. ORTEA products are built with suitable quality components and that the manufacturing process is constantly verified in accordance with the Quality Control Plans which the Company applies in compliance with the ISO 9001 Standards. The commitment towards environmental issues and safety at work issues is guaranteed by the certification of the Management System according to the ISO14001 and OHSAS18001 Standards. In order to obtain better performance, the products described in the present document can be altered by the Company at any date and without prior notice. Technical data and descriptions do not hold therefore any contractual value.